

Product name:

NKG21

Operating limits:

Pressure: 10 Bar

Speed: 10 m/s

Temperature: -30°C... + 200°C



Specifications:

Type	d1	d3	d7	L1	L3
NKG21-16	16	26	27	15	12
NKG21-18	18	32	33	20	13.5
NKG21-20	20	34	35	20	13.5
NKG21-22	22	36	37	20	13.5
NKG21-24	24	38	39	20	13.3
NKG21-25	25	39	40	20	13
NKG21-28	28	42	43	26	12.5
NKG21-30	30	44	45	26	12
NKG21-32	32	46	48	26	12
NKG21-33	33	47	48	26	12
NKG21-35	35	49	50	26	12
NKG21-38	38	54	56	30	13
NKG21-40	40	56	58	30	13
NKG21-43	43	59	61	30	13
NKG21-45	45	61	63	30	13
NKG21-48	48	64	66	30	13
NKG21-50	50	66	70	30	13.5
NKG21-53	53	69	73	30	13.5
NKG21-55	55	71	75	30	13.5
NKG21-60	60	80	80	33	13.5
NKG21-65	65	85	85	33	13.5
NKG21-70	70	90	92	33	14.5
NKG21-75	75	99	97	40	14.5

- ☐ Stationary Ring (Ceramic/SIC/TC)
- ☒ Rotary Ring (Carbon/SIC/TC)
- ☐ O-Ring and Bellows (NBR/VITON)
- ☐ Spring (SUS304/SUS316)

