

S1

Product name:

Operating limits:

Pressure: 6 Bar

Speed: 15 m/s

Temperature: -30°C... + 200°C



Specifications:

Type	d1	d2	d3	d5	d7	L1	L3	L4
A2 3/8	11	24	29	12	23	17	4	7
A2 1/2-2850	14.2	28.55	32	14	25	18.2	5	8
94366-700	14.2	30	35	15	24	18	5	8
A2 1/2-3550	14.2	33.4	38	14	25	18	5	6.7
1118-A737	17.2	36.5	39.5	17	25.8	18.2	5.5	7.2
1118-A707	17.2	36.5	41	17	33.2	20.5	5.5	8.5
1118-A706	17.2	36.9	42	17	31.5	17	5.5	9
1103/161	17.5	35.6	39.5	17	33	20.5	5.5	8.5
A2 5/8	18.2	36.45	41.5	18	31	19.8	5	8
1117/178	18.2	38.1	41.5	18	31	19.8	5	8
A2 3/4-38	21.2	38	43.8	21	35	20.5	5	9.5
A2 3/4-40F	21.2	40	43.8	21	35	20.5	5	9.5
A2 1/2-46	26.4	46	51	29	44	25	7	10
A2 1/2-47	26.4	47	51	29	44	25	7	10
A2 1/2-52L	26.4	52	57	27	48	25	7	12
A2-3052	31	52	57	32	48	27	8	11

-  Rotary Ring (Ceramic/SIC/TC)
-  Stationary Ring (Carbon/SIC/TC)
-  Secondary Seal (NBR/EPDM/VITON)
-  Spring and Other Parts (S.S/US304/SUS316)

